

### Product Information

Applicable product:				
Bath whirlpool, custom pump	K-1368-HF			
Bath whirlpool, custom pump	K-1369-HN			
Fixture*:				
Basin area:				
Bathing well	48" (121.9 cm) x 29" (73.7 cm)			
Top area	66" (167.6 cm) x 36" (91.4 cm)			
Weight	170 lbs (77.1 kg)			
To overflow:				
Water depth	18" (45.7 cm)			
Capacity	118 gal (446.7 L)			
* Approximate measurements for comparison only.				
Pump:	kW	V	Hz	A
Variable speed:	1.5	240	50/60	11
Required accessories:				
Jet trim kit	K-9696			

### Required Electrical Service

Dedicated circuit required, protected with Class A Ground-Fault Circuit-Interrupter (GFCI) or Residual Current Device (RCD):	
Pump/control	220/240 V, 11 A, 50/60 Hz

### Installation Notes

Install this product according to the installation guide.

Floor support under whirlpool must provide for a minimum of 56 lbs/square foot (274 kg/square meter) loading.

Hot water supply should be 70% of capacity or greater. Installations will vary.

If installing a rim-mount faucet, make sure there is no interference with drain overflow and circulating system before drilling any holes. Consult local and national codes for minimum air gap requirements if installing a spout on the faucet deck.

Pump must be relocated to custom position at the time of installation. Provide adequate clearance.

Fixture conforms to ANSI Standard Z124.1.2. All dimensions are nominal.

