

HERITAGE 5' X 42"™ WHIRLPOOL

- 2805.018WC Whirlpool Featuring System I:**
- Acrylic with fiberglass reinforcement
 - EverClean™ whirlpool system featuring Antimicrobial AlphaSan®
 - Pre-leveled tub bottom
 - Dual, molded-in arm rests
 - Integral faucet deck area
 - 1.5 HP single speed, self-draining pump/motor
 - Factory installed power cord and plug
 - Six multi-directional and flow-adjustable jets including:
 - Two Ideal-flow jets
 - Four body massage jets
 - Deck-mounted air switch On/Off
 - Two silent air volume controls
 - Quick Connect Safe-T-Heater connection system
 - Factory installed and tested whirlpool system

- 2805.028WC Whirlpool Massage Featuring System II:**
- Same as 2805.018WC except:
- 2.0 HP, two speed self-draining pump/motor with dry run seal and Pulse feature
 - Deck-mounted electronic On/Off with 20 minute built-in timed safety shut off and chrome bezel

Nominal Dimensions:

1524 x 1067 x 546mm
(60" x 42" x 21-1/2")

Compliance Certifications -

Meets or Exceeds the Following Specifications:

- Underwriters Laboratories - Hydromassage Bathtubs UL 1795
- ASME A112.19.7M for Whirlpool Appliances
- ANSI Z124.1 for Plastic Bathtubs
- ASTM E162 for Flammability
- NFPA 258 for Smoke Density

SEE REVERSE FOR ROUGHING-IN DIMENSIONS
AND PRODUCT SPECIFICATIONS



To Be Specified - Required:

- Color:
- Bath Filler: (specify finish)
- Bath Drain: 1583.470 (specify finish)

To Be Specified - Optional:

- Safe-T-Heater*: 9075.120
- Heritage 5' Apron: 9160.2800 (specify color)
- Grab Bar Kit: 9822-100-one per kit (specify color)
- System II Control Bezel: 9861.100 (specify finish)

For color/finish availability and other faucet choices, please see the Product Selector and Pricing Guide.

* **NOTE:** the Safe-T-Heater is designed to maintain water temperature during operation. It will not heat cold water to desired bathing temperature.

