

**LAKELAND™ 33" LARGE SINGLE BOWL
KITCHEN SINK**

- Americast® brand engineered material
- Single bowl design
- Acid-resisting glossy porcelain finish
- Top mount or undercounter installation
- Silicone sealant supplied
- Available in 0, 1, 3, 4 or 5 faucet hole configuration
- Customized Hole Punching Available (See Holes page KS-61)

Top Mount/Undercounter:

- 7193.000** No Holes
- 7193.001** 1 Center Hole
- 7193.803** 3 Holes
- 7193.804** 4 Holes
- 7193.805** 5 Holes

Undercounter Installation Order:

- 791123-100** Mounting Kit (consists of cut-out templates and mounting clips)

Nominal Dimensions:

838 x 559 x 241mm
(33" x 22" x 9-1/2")

Bowl sizes:

679mm (26-3/4") wide
413mm (16-1/4") front to back
229mm (9") deep

Compliance Certifications -

Meets or Exceeds the Following Specifications:

- ASME A112.19.4M for Americast Plumbing Fixtures
- ASTM E162 for Flammability
- NFPA 258 for Smoke Density



Shown with **4114.100** Lakeland Pull-Out Kitchen Faucet

To Be Specified:

- Color:
- Faucet*:
- Faucet Finish:
- Basket Strainer: 4331.013
- Trap:


Optional Accessories:

- Basin: 8193.300
- Bottom Sink Rack: 8193.120
- Cutting Board: 8193.200
- Dish Rack with Two Utensil Holders and Colander Kit: 8193.400
- Under Cabinet Storage: 8193.140

* See faucet section for available models

SEE REVERSE SIDE FOR ROUGHING-IN DIMENSIONS

7193.001/803/4/5 Top Mount



NOTES:

* COUNTERTOP CUTOUT for NEW INSTALLATIONS

756mm X 527mm with 25mm Radius
 (29-3/4" X 20-3/4" WITH 1" RADIUS)

* COUNTERTOP CUTOUT for REPLACEMENT INSTALLATIONS

756mm to 806mm X 527mm with 25mm Radius
 (29-3/4" to 31-3/4" X 20-3/4" WITH 1" RADIUS)

FITTINGS NOT INCLUDED AND MUST BE ORDERED SEPARATELY.

PROVIDE SUITABLE REINFORCEMENT FOR ALL WALL AND COUNTERTOP SUPPORTS.

IMPORTANT: Dimensions of fixtures are nominal and may vary within the range of tolerances established by ASME Standard A112.19.4. These measurements are subject to change or cancellation. No responsibility is assumed for use of superseded or voided leaflet.

NOTES:

● Recommended minimum countertop thickness:

Wood - 19mm (3/4")

Marble and Solid Surface - 12mm (1/2")

* TEMPLATE PROVIDED WITH MOUNTING KIT 791123-100 FOR UNDERCOUNTER, INSTALLATION AND COUNTERTOP CUTOUT.

FITTINGS AND UNDERCOUNTER MOUNTING KIT NOT INCLUDED AND MUST BE ORDERED SEPARATELY.

PROVIDE SUITABLE REINFORCEMENT FOR ALL WALL AND COUNTERTOP SUPPORTS.

IMPORTANT: Dimensions of fixtures are nominal and may vary within the range of tolerances established by ASME Standard A112.19.4. These measurements are subject to change or cancellation. No responsibility is assumed for use of superseded or voided leaflet.

7193.001/803/4/5 Undercounter Mount

