





ASSEMBLY INSTRUCTION

MODEL # 31367-05

NOTE: Please consult a qualified electrician if you are not certain of the installation.

CAUTION: Before starting the installation, disconnect the power by turning off the circuit breaker or by removing the fuse at the fuse box.

1. Thread mounting screws completely into mounting ring, in the opposite direction of the green ground screw.
2. Use electric drill (not included) to drill two holes on wall then push two plastic wall anchors into wall. Fasten enforced mounting ring to ceiling, using 2 wood screws into plastic wall anchors and 2 outlet box screws into junction box.
3. Weave electrical wires and ground wire through loop. Screw loops of rods to the nipple on top of fixture outlet box.
4. Using two pliers, twist open one link at the end of the chain. Hook it to the rod and close the link. Place a piece of cloth between the pliers' jaws and the chain link to prevent scratching the link finish.
5. Attach tubes and arms to the screws on fixture outlet box, and tighten round finials.
6. Place the arms onto fixture cage and make sure the holes of the fixture cage and arms are overlapped. Place screws through two holes, and tighten round finial.
7. Place the nipple of bottom finial through hole on the fixture outlet box, and tighten top finial.
8. Place glass and socket sleeves to sockets, and tighten socket rings.
9. Using two pliers twist open the link at the other end of the chain. Hook the whole fixture to the loop on canopy and close the link.
10. Weave the fixture wires up through the chain links, through loop on canopy, through canopy. Note that the copper ground wire must be woven through every third link of chain. Position both the junction box supply wires and the fixture wires outside of the junction box to facilitate connection.
11. Twist stripped ends together with pliers, the wire with writing on it to the power wire (black) and the wire without writing on it to neutral wire (white). Snip ends. Cover the connections using the wire connectors provided with the fixture. Tie the ground wires from junction box and from fixture to the green ground screw on the mounting strip. After connection is completed, carefully position wires back inside junction box.
12. Place the canopy over the mounting screws all the way to the ceiling and tighten the cap nuts onto the mounting screws until the canopy is firmly held against the ceiling.
13. Place hooks onto fixture cage.
14. Install light bulbs (not included). Use only bulbs of the specified type and maximum rated wattage or less.
15. Turn on the power and you can enjoy your new light.