

15007AEBM


1X13W Double Twin Fluorescent 5" IC Airtight Universal Housing Recessed Downlight & Trims

NEW
MULTI-TAP
ELECTRONIC
BALLAST

- Flexible, reliable and easy to install.
- Designed for providing accent and task lighting.
- IC rated. For installations where housing will be in direct contact with insulation.
- The 15007A housing is Washington State energy code approved to meet restricted airflow requirements.
- Airtight housing limits the exchange of air between ceiling plenum and heated/cooled areas.
- One 13W double twin tube, G24Q-1 (not included).

HOUSING FEATURES

- Integral thermal protector guards against misuse of insulation materials and improper lamping.
- Socket clips into trim bracket for 90° vertical alignment of lamp socket.
- Two socket height positions on trim allow adjustment for light control and output.
- Junction box is listed for through branch circuit wiring and has several 1/2" knockouts. Four Romex knockouts include integral strain relief and require no additional clamps.



15007AEBM 120/277v Multi-Tap Electronic Ballast

Size: W 5.5" x L 10" x H 7.5"
Aperture: 4.25"

- Reinforced captive bar hangers allows housing to be positioned at any point within a 24" joist span and then locked in place with a set nail. NICOR's self-aligning hanger bar with its unique lip design helps align can to joist. Four double-headed captive nails provide for ease of installation.
- Bar hangers can be repositioned 90° on the plaster frame without tools.
- Electronic Ballast.

INSTALLATION FEATURES

- 7 1/2" height allows use in 2" x 8" joist construction.
- Housing adjusts to accommodate ceiling thickness.
- Supplied with 3 push-in wire connectors for ease of installation.

LISTINGS

- UL listed for direct contact with insulation.
- UL damp location.
- UL feed through.
- CUL approved.

