

# 15007AR 1X13W Double Twin Fluorescent 5" IC Airtight Remodel Housing Recessed Downlight & Trims

Economy Series

- Flexible, reliable and easy to install.
- Designed for providing accent and task lighting.
- IC rated. For installations where housing will be in direct contact with insulation.
- The 15007AR housing is Washington State energy code approved to meet restricted airflow requirements.
- Airtight housing limits the exchange of air between ceiling plenum and heated/cooled areas.
- One 13W double twin tube, Gx23-2 (not included).

## HOUSING FEATURES

- Integral thermal protector guards against misuse of insulation materials and improper lamping.
- Socket clips into trim bracket for 90° vertical alignment of lamp socket.
- Two socket height positions on trim allow adjustment for light control and output.

- Junction box is listed for through branch circuit wiring and has several 1/2" knockouts. Four Romex knockouts include integral strain relief and require no additional clamps.
- Magnetic Ballast.

## INSTALLATION FEATURES

- 7 1/2" height allows use in 2" x 8" joist construction.
- Unit slips through a 5 3/8" ceiling opening.
- Four remodel clips secure housing and accommodate ceiling thickness.
- Supplied with 3 push-in wire connectors for ease of installation.

## LISTINGS

- UL damp location.
- UL feed through.
- UL listed for direct contact with insulation.



## 120v Magnetic Ballast

Size: W 5.5" x L 13" x H 7.5"

Aperture: 4.25"

