



Assembly & Installation Instructions

CAUTION:

1. TURN OFF THE ELECTRICITY AT THE FUSE BOX OR CIRCUIT BREAKER BEFORE INSTALLATION.
2. RISK OF FIRE: DO NOT LAMP FIXTURE GREATER THAN THE MAXIMUM WATTAGE SHOWN ON THE WATTAGE LABELS ON THE FIXTURE.
3. IF YOU ARE UNFAMILIAR WITH ELECTRIC WIRING, CONSULT A QUALIFIED ELECTRICIAN TO INSTALL THIS FIXTURE FOR YOU.

FOR POST MOUNT

- 1.-Disconnect power at main electrical panel before installation.
- 2.-Pull black, white and ground wires out of post cup.
- 3.-Following wiring instruction carefully (listed below)
- 4.-After wires are connected, tuck them carefully inside the post. Align the lantern with post and secure with sheet metal screws.
- 5.-Screw center tube into coupler until secure and install light bulbs (not included). See relamping label at candle tube for type and maximum allowed wattage, then put back top cap & top finial in sequence and tighten with finial (See attached respective drawing).

Wiring

1. Split the conductors of the **fixture wire** about 6 inches. Being careful not to expose any of the wire inside of the insulation.
2. Connect the **fixture ground wire** to the **outlet box ground wire** using wirenut (not provided). Connect **outlet box ground wire** to **mounting plate** with **GREEN hex-head ground screw** to tapped hole in **mounting strap** marked "GND"
3. Connect the half of the **fixture wire** that is white, marked, or has a ribbed surface to the **outlet box supply wire (WHITE)**. Connect the other half of the **fixture wire** that is black, unmarked, or has a smooth surface to the **outlet box supply wire (BLACK or RED)**. Use **wirenuts** provided.

