





8750 LED Ceiling Recess W/O Baffle, W/O Housing

- 1.2W x 12 SSC P4 LEDs | 15° Beam Angle
- 5.51" trim diameter
- Ceiling opening diameter: 4.75"
- Swivel range: 15°
- Class II wiring with quick connector
- Requires 350mA constant current LED driver (NOT included)

SSC P4 LED 1.2W X 12 15°		
H(m)	E(Lx) 2x8°	D(m)
1m	3458	0.28
2m	865	0.56
3m	384	0.84
4m	216	1.12



***LED Color Temperature**

- Cool White (C) 5800K
- Natural White (N) 4000K
- Warm White (W) 2800K

* ± 3% Kelvin temperature variation

All fixtures and lighting systems must be used with Prima transformer, driver, and/or ballast; or all warranties are void.

ITEM #	DESCRIPTION	HARDWARE	LED COLOR	LAMP
<input type="checkbox"/> 8750	6" LED gimbal downlight	<input type="checkbox"/> BK - Black <input type="checkbox"/> PC - Polished Chrome <input type="checkbox"/> PG - Polished Gold <input type="checkbox"/> SV - Silver <input type="checkbox"/> WH - White	<input type="checkbox"/> C - Cool White <input type="checkbox"/> N - Natural White <input type="checkbox"/> W - Warm White	<input type="checkbox"/> 1.2W x 12 SSC P4 LEDs, 15° Beam Angle