



Project: \_\_\_\_\_

Fixture Type: \_\_\_\_\_

Location: \_\_\_\_\_


Contact/Phone: \_\_\_\_\_

# 6" VERTICAL IC COMPACT FLUORESCENT REMODEL HOUSING

26W COMPACT FLUORESCENT LAMP

T24  
2005
**ICPL626RE**  
**ICPL626REN**

## PRODUCT DESCRIPTION

ICPL Energy Star, Air-Loc® sealed remodel housing • Can be completely covered with insulation • When used with Air-Loc Gasket (see accessories), stops infiltration and exfiltration of air, reducing heating and air cooling costs • Trims shown with Air-Loc symbol  do not require a gasket • 2 year warranty.

## PRODUCT SPECIFICATIONS

**Lamp** One 26W triple tube (4-pin) CFL lamp.

**Socket** Supplied with spring to accommodate certain trim installations, or can be attached to top of housing for certain trims.

**Ballast** 120V HPF or NPF Rapid Start Electronic with end-of-life lamp protection • Optional dimming ballast available (Title 24 compliant, Energy Star qualified) • UL listed/CSA certified.

**Trims** Trim selection shown on reverse.

**Labels** Energy Star qualified • Meets Washington State Air Tight Requirements, IECC • Complies with FCC Part 18 consumer use limits • Product mechanically protected against improper use of lamps • Union made AFL-CIO • Complies with California's Title 24 energy code • Trims 220, 239, 241, 242, 243, 271, 2330, 6101 and 9900 are wet location approved for covered ceiling applications.

**Testing** All reports are based on published industry procedures; field performance may differ from laboratory performance.

Product specifications subject to change without notice.

## INSTALLATION



**Junction Box** Pre-wired junction box provided with removable access plate, (5) ½" knockouts, (4) Romex connectors and ground wire • Knockouts equipped with pryout slots.

**Housing** .032" aluminum housing • Remodel springs accommodate up to 1 ½" ceiling thickness.

## PRODUCT CODES

Catalog Number	Input Voltage	Lamp Rating (max.)	Ballast
<b>ICPL626RE</b>	120V	26W Triple Tube (4-pin) CFL	HPF
<b>ICPL626REN</b>	120V	26W Triple Tube (4-pin) CFL	NPF

## DIMENSIONS



6 3/4" CEILING CUTOUT

## ACCESSORIES

Catalog No.	Description
<b>ALG6R</b>	Air-Loc Gasket

To order, specify catalog number.

## OPTIONS

(Add as suffix to housing)

Suffix No.	Description
<b>-DB120</b>	120V NPF Dimming Ballast (for use with ICPL626REN only)

Note: This product is Energy Star qualified and Title 24 compliant.

Ordering Example: ICPL626REN-**DB120**

# 6" VERTICAL IC COMPACT FLUORESCENT REMODEL HOUSING

## 26W COMPACT FLUORESCENT LAMP

### ICPL626RE ICPL626REN

#### TRIMS/LAMPS

	Cat. No.	Description	Lamp Rating
	 <b>220-WH</b> ◆ <b>220-PW</b> ◆	Albalite lens with Reflector Shower/Closet Light	26W Triple Tube (4-pin) CFL
	 <b>241-WH</b> ◆ <b>241-PW</b> ◆	Drop Opal with Reflector Shower/Closet Light	26W Triple Tube (4-pin) CFL
	 <b>242-WH</b> ◆ <b>242-SC</b> ◆ <b>242-ABZ</b> ◆	Shower Trim, Frosted Lens with Clear Center Shower Trim, Frosted Lens with Clear Center Shower Trim, Frosted Lens with Clear Center	26W Triple Tube (4-pin) CFL
	 <b>243-WH</b> ◆	Decorative Swirl Etched Opal Glass	26W Triple Tube (4-pin) CFL
	 <b>239-WH</b> ◆	Frosted Lens with Reflector	26W Triple Tube (4-pin) CFL
	 <b>271-PW</b> ◆	Drop Opal with Reflector	26W Triple Tube (4-pin) CFL
	 <b>28W-WH</b> <b>28B-WH</b>	Conical White Baffle Conical Black Baffle	26W Triple Tube (4-pin) CFL
	 <b>29C-WH</b> <b>29W-WH</b>	Deep Cone - Clear Deep Cone - White	26W Triple Tube (4-pin) CFL
	 <b>232C-WH</b> <b>232G-WH</b> <b>232W-WH</b> <b>232HZ-WH</b> <b>232WHZ-WH</b>	Multiplier - Clear Alzak® Multiplier - Gold Alzak® Multiplier - Gloss White Multiplier - Haze Multiplier - Wheat Haze	26W Triple Tube (4-pin) CFL*
	 <b>2320C-WH</b> <b>2320HZ-WH</b> <b>2320WHZ-ABZ</b> <b>2320WHZ-WH</b>	Multiplier in Clear Low Iridescent Alzak® Multiplier in Haze Multiplier in Wheat Haze Multiplier in Wheat Haze	26W Triple Tube (4-pin) CFL
	 <b>233C-WH</b>	Multiplier in Clear Alzak® with Black Baffle, White Trim	26W Triple Tube (4-pin) CFL
	 <b>261W-WH</b> <b>261B-WH</b>	Scoop Wall Wash with White Baffle Scoop Wall Wash with Black Baffle	26W Triple Tube (4-pin) CFL
	 <b>2330W-WH</b> ◆ <b>2330B-WH</b> ◆	White Baffle, Regressed Frosted Dome Lens with Reflector Black Baffle, Regressed Frosted Dome Lens with Reflector	26W Triple Tube (4-pin) CFL
	 <b>6101-ABZ</b> ◆ <b>6101-SC</b> ◆ <b>6101-WH</b> ◆	Beveled Frame - Frosted Dome Lens with Reflector Beveled Frame - Frosted Dome Lens with Reflector Beveled Frame - Frosted Dome Lens with Reflector	26W Triple Tube (4-pin) CFL
	 <b>9900-WH</b> ◆	Fluted Drop Opal Lens	26W Triple Tube (4-pin) CFL*


Trim Size: Catalog Numbers 242, 243, 239, 271, 28, 29, 232, 2320, 233, 261, 9900 - 7 $\frac{5}{8}$ " O.D. Catalog Numbers 220, 241 - 8" O.D. Catalog Number 2330 - 7 $\frac{3}{4}$ " O.D. Catalog Number 6101 - 7 $\frac{3}{4}$ " O.D.

Trim Finish: ABZ - Classic Aged Bronze, PW - Plastic White (Polycarbonate material shower trim), SC - Satin Chrome, WH - White.

Alzak is a registered trademark of Alcoa Corp.

Note: In Canada when insulation is present, Type IC fixtures must be used.

\*Specify General Electric or Osram/Sylvania lamps only.

 JUNO IC housings meet IECC Energy Code requirements per ASTM E283.  
Air-Loc® rated trims are pre-gasketed for minimum air leakage with IC housings.

◆ UL Listed for use in wet location.



1300 S. Wolf Road • P.O. Box 5065 • Des Plaines, IL 60017-5065 • Phone (847) 827-9880 • Fax (847) 827-2925

220 Chrysler Drive • Brampton, Ontario • Canada L6S 6B6 • Phone (905) 792-7335 • Fax (905) 792-0064

Visit us at [www.junolightinggroup.com](http://www.junolightinggroup.com)

Printed in U.S.A. ©2007 Juno Lighting, Inc.