

BLS400AW16DL/UP

DESCRIPTION

16" and 22" Low Bays. Spun semi-specular anodized aluminum.

SPECIFICATIONS

Ballast:

Quad-Tap CWA Ballast (120/208/240/277

Mounting:

Die cast aluminum painted white. 3' cord and hook/loop. Heavy-duty sheet metal wiring box with 1/2 knockouts and easy leveling adjustment.

Junction Box:

Heavy duty stamped steel junction box.

Patterns:

Field adjustable light distribution patterns

Plate:

Die-cast plate tapped 3/4" NPS accepts 3/4" pipe or 715NEW die cast hook

Reflector:

Spun semi-specular gloss white aluminum

Restrike Time:

10 - 20 minutes

Socket:

4KV pulse rated mogul base socket

Start Up Time:

3 - 5 minutes

UL Listing:

Suitable for damp locations. UL and cUL listed for 40°C (104°F) ambient temperature

Wiring Compartment:

Removable steel wiring compartment door for quick and easy mounting

Drop Lens:

Clear acrylic fastened with clamp band

Lamp:

Mogul Base, ED18

Patents:

RAB sensor and fixture designs are protected under U.S. and International Intellectual Property laws.

Color:

White

Weight:


0

DIMENSIONS



PHOTOMETRIC

BLS400AW16DL



ZONAL LUMEN SUMMARY			
Zone	Lumens	%Lamp	%Fixture
0-30	6245	12.5	18.7
0-40	11203	22.4	33.6
0-60	24182	48.4	72.5
0-90	32897	65.4	98.0
90-120	622	1.2	1.9
90-130	654	1.3	2.0
90-150	654	1.3	2.0
90-180	654	1.3	2.0
0-180	33352	66.7	100.0

Total Rated Lamp Lumens = 50000
Total Luminaire Efficiency = 66.7%
Spacing Criteria (0-180) = 1.66, (90-270) = 1.66

ORDERING INFORMATION

High Pressure Sodium
Lamp supplied with fixture

Total Watts	Lamp Type	Lamp Base	Ballast
400			

Starting Amps/ Operating Amps			
120V	208V	240V	277V

Input Watts	LAMP ANSI	Initial Lumens	Lamp Hours
0			

Factory Installed Options
Add suffix to Catalog Number

Note: Specifications may change without notice