

# Rigid Standoff with Connector



Shown approximately 25% actual size.

### DESCRIPTION


The field-cutable rigid standoff with connector is used to join sections of Two-Circuit T~trak™ track together end to end while supporting the system. Order one for each connection point between track sections. Use conductive type to continue power through connection. Use isolating type to isolate multiple circuits on one continuous run. Select the appropriate length to match the specified drop for the system.

### FINISH

Antique bronze, satin nickel, white.

### WEIGHT

0.55-2.95 lb./0.26-1.33 kg. ±



### ORDERING INFORMATION

700TT2S	TYPE	LENGTH (A)	FINISH
	CC CONDUCTIVE	02 2"	Z ANTIQUE BRONZE
	IC ISOLATING	06 6"	S SATIN NICKEL
		12 12"	W WHITE
		24 24"	
		36 36"	
		48 48"	
		96 96"	

**T~trak™**  
a brand of **TECH LIGHTING®**

7400 Linder Avenue T 847.410.4400  
Skokie, Illinois 60077 F 847.410.4500

www.ttraklighting.com

January 2007 Specifications subject to change without notice.

ttz\_rig\_stdf\_con\_spec.pdf



700TT2S \_\_\_\_\_

FIXTURE TYPE: \_\_\_\_\_

JOB NAME: \_\_\_\_\_