


INSTALLATION AND WIRING DIAGRAM

USA

LEDRA

LEDRA™ 40W Driver

ART. NO. 70418 DC DRIVER



IMPORTANT SAFETY INSTRUCTIONS



1. THIS PRODUCT MUST BE INSTALLED BY A PERSON FAMILIAR WITH THE CONSTRUCTION AND OPERATION OF THE PRODUCT AND THE HAZARDS INVOLVED, IN ACCORDANCE WITH THE LOCAL AND NATIONAL CODE.
2. DRY LOCATIONS ONLY.
3. SUITABLE FOR SUSPENDED CEILING.
4. LED'S MAY BE DAMAGED IF YOU DO NOT WIRE WITHIN THE REQUIRED NUMBER RANGE OF FIXTURES.
5. Turn off power prior to any work on the systems.
6. Warranty is void in case of unauthorized modifications and/ or improper use.

READ ALL OF THESE INSTALLATION INSTRUCTIONS BEFORE INSTALLING THE FIXTURE

Operating Temperature -22° to 140° F

- 40W Driver fits in standard 4 x 4 J-Box.

- Powers 6 to 10 Ledra fixtures (Not for use with Ledra track).

- Fixtures must be wired to the driver in series.

- Driver may be placed up to 150 ft from fixtures 100-240VAC.

- Purple wire is + and Black wire is -.

- **Do Not use with 5 or less fixtures.**

- **LED's may be damaged if you do not wire within the required number range of fixtures.**

